



(19)

(11) Publication number: 59

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: 57230095

(51) Intl. Cl.: H01L 21/31 H01L 21/203

(22) Application date: 28.12.82

(30) Priority:

(43) Date of application
publication: 17.07.84(84) Designated contracting
states:

(71) Applicant: FUJITSU LTD

(72) Inventor: KURAHASHI TOSHIO



(74) Representative:

(54) FORMATION OF THIN
FILM

(57) Abstract:

PURPOSE: To flatten and smooth the surface of a deposited film in a stabilized manner by a method wherein a rotating sample and either of a deposition film material or an ion gun are arranged facing each other, the other party is arranged facing the surface of the sample from the side face of either of them, and simultaneously with the deposition of a thin film, a thin film is coated while it is coated on the surface of the raised part of the sample is being removed by an ion.

CONSTITUTION: A PSG substrate target 3 is arranged facing the front surface of the sample substrate 2 which rotates at several hundreds revolution per minute in a reaction chamber 1 is arranged facing the front surface of the sample substrate 2, an ion gun 4 is arranged facing the surface of the sample substrate on the lateral side of the target 3, and the ion gun 4 is maintained at the angle of 45° to 70° to the sample substrate surface. The



to the sample substrate surface. The sample substrate 2 consists of an aluminum wiring layer 21 provided on a silicon substrate 20, and when a PSG film 22 is coated on said PSG film 22 is thinly coated by and by on a wiring layer 21 by the repetition of coating by sputtering and the etching using the ion gun, and also the PSG film 22 is thickly coated on the substrate 20 located at the recessed part. This is because an etching is performed intensively on the raised part by the ion gun, the wiring layer 21 is buried and the PSG film having flat surface can be obtained.

COPYRIGHT: (C)1984,JPO&Japio

Glie

Delphion **Intellectual Property Network**

To Search & Research

[IPN Home](#) | [Search](#) | [Order](#) | [Shopping Cart](#) | [Login](#) | [Site Map](#) | [Help](#)**Patent Plaques**Recognize
the achievement

Country

Kind

Inventor(s)

Applicant(s)

Issued/Filed Dates

Application Number

IPC Class

Abstract

Other Abstract Info

Foreign References

Powered by DB2
and Net.DataNominate this
invention
for the Gallery...**JP59123236A2: FORMATION OF THIN FILM**[View Images \(1 pages\)](#) | [View INPADOC only](#)

JP Japan

**KURAHASHI TOSHIO****FUJITSU LTD**[News, Profiles, Stocks and More about this company](#)

July 17, 1984 / Dec. 28, 1982

JP1982000230095**H01L 21/31; H01L 21/203**

Purpose: To flatten and smooth the surface of a deposited film in a stabilized manner by a method wherein a rotating sample and either of a deposition film material or an ion gun are arranged facing each other, the other party is arranged facing the surface of the sample from the side face of either of them, and simultaneously with the deposition of a thin film, a thin film is coated while it is coated on the surface of the raised part of the sample is being removed by an ion.

Constitution: A PSG substrate target 3 is arranged facing the front surface of the sample substrate 2 which rotates at several hundreds revolution per minute in a reaction chamber 1 is arranged facing the front surface of the sample substrate 2, an ion gun 4 is arranged facing the surface of the sample substrate on the lateral side of the target 3, and the ion gun 4 is maintained at the angle of 45W70° to the sample substrate surface. The sample substrate 2 consists of an aluminum wiring layer 21 provided on a silicon substrate 20, and when a PSG film 22 is coated on said PSG film 22 is thinly coated by and by on a wiring layer 21 by the repetition of coating by sputtering and the etching using the ion gun, and also the PSG film 22 is thickly coated on the substrate 20 located at the recessed part. This is because an etching is performed intensively on the raised part by the ion gun, the wiring layer 21 is buried and the PSG film having flat surface can be obtained.

COPYRIGHT: (C)1984,JPO&Japio

none

(No patents reference this one)

**Alternative
Searches**[Patent Number](#)[Boolean Text](#)[Advanced Text](#)**Browse**[U.S. Class
by title](#)[U.S. Class
by number](#)[IBM Technical
Disclosure Bulletin](#)



[Privacy](#) | [Legal](#) | [Gallery](#) | [IP Pages](#) | [Advertising](#) | [FAQ](#) | [Contact Us](#)